

California Institute of Technology
Department of Computer Science
Computer Architecture

CS184b, Winter 2000

Assignment 1: Pipelined ISA

Tuesday, January 16

Due: Tuesday, January 23, 5:00PM

Part A

Work the following problems from Hennessey and Patterson:

- 3.1
- 3.4
- 3.6
- 3.10

Part B

1. For your program chosen in assignment #2, estimate its CPI and hence running time based on the data from `sim-profile`.
 - assume a pipeline structure like the DLX in chapter 3.
 - assume perfect memory system for now
 - use the aggregate data on instruction, branch, load frequency which you get from `sim-profile` and assume an uniform distribution of instructions, etc.
 - state additional assumptions which you need to make in your calculation
 - show your calculations
2. Run your program under `sim-outorder` in an “inorder” mode and report the running time / CPI.
 - My best guess at a configuration which might come close to modeling a simple, pipelined, scalar processor is given in `/cs/courses/cs184/assign/b3/sim-outorder.invoke`; I’ve only played with this a little myself, so if you’re motivated to look at it more and think there’s a better configuration, use it and let me know. I’m hoping the separated, 64K direct-mapped L1 caches will hold your probably so we’ll see minimal cache effects here (statistical output from `sim-outorder` will help you verify this assumption or any changes you need to make so it will become true).
 - I have no reason to believe this is that close to what you are calculating above, so don’t worry if they’re different.
 - We’ll be looking at all these ILP and cache issues in weeks ahead, so this exercise is just giving you a chance to use the detailed simulator and develop a base of reference for later experiments where we look at these effects.